

M10-SPLX SERIES

Features

- . Output off function
- . New panel design
- . 5V/1A fixed output

Specifications

- . Line Regulation: $CV \leq 1 \times 10^{-4} + 3mV$ $CC \leq 2 \times 10^{-3} + 3mA$
- . Load Regulation: $CV \leq 1 \times 10^{-4} + 2mV$ $CC \leq 2 \times 10^{-3} + 3mA$
- . Ripple & Noise: $CV \leq 0.5mV$ rms $CC \leq 3mA$ rms
- . Display Accuracy: Voltmeter $\pm(0.2\%Rdg + 2$ digits)
Ammeter $\pm(1.0\%Rdg + 2$ digits)
- . Input Voltage: 110 ~ 127VAC $\pm 10\%/60Hz$, 220 ~ 240VAC $\pm 10\%/50Hz$
Switchable



M10-SP3003LX

Model	Voltage	Current	Fixed output	Dimensions(W×H×D)	Weight(kg)
M10-SP3003LX	0~30V	0~3A	5V/1A	130×160×310mm	5
M10-SP3005LX	0~30V	0~5A	5V/1A	130×160×310mm	6.3
M10-SP6003LX	0~60V	0~3A	5V/1A	130×160×310mm	6.5

M10-TPH SERIES

Features

- . Voltage/Current preset function
- . New panel design
- . Two adjustable outputs & one fixed output
- . Cooling with the fan at back (M10-TP3005H)

Specifications

- . Line Regulation: $CV \leq 1 \times 10^{-4} + 3mV$
 $CC \leq 2 \times 10^{-3} + 3mA$
- . Load Regulation: $CV \leq 1 \times 10^{-4} + 2mV$
 $CC \leq 2 \times 10^{-3} + 3mA$
- . Ripple & Noise: $CV \leq 0.5mV$ rms
 $CC \leq 3mA$ rms
- . Display Accuracy: Voltmeter $\pm(0.2\%Rdg + 2$ digits)
Ammeter $\pm(1.0\%Rdg + 2$ digits)
- . Input Voltage: 110 ~ 127VAC $\pm 10\%/60Hz$, 220 ~ 240VAC $\pm 10\%/50Hz$
Switchable



M10-TP3003H

Model	Voltage	Current	Fixed output	Dimensions (W × H × D)	Weight (kg)
M10-TP3003H	0~30V×2	0~3A×2	5V/3A	260×160×370mm	8
M10-TP3005H	0~30V×2	0~5A×2	5V/3A	260×160×370mm	10