

## M10-SPLX SERIES

### Features

- . Output off function
- . New panel design
- . 5V/1A fixed output

### Specifications

- . Line Regulation:  $CV \leq 1 \times 10^{-4} + 3mV$   $CC \leq 2 \times 10^{-3} + 3mA$
- . Load Regulation:  $CV \leq 1 \times 10^{-4} + 2mV$   $CC \leq 2 \times 10^{-3} + 3mA$
- . Ripple & Noise:  $CV \leq 0.5mV$  rms  $CC \leq 3mA$  rms
- . Display Accuracy: Voltmeter  $\pm(0.2\%Rdg + 2$  digits)  
Ammeter  $\pm(1.0\%Rdg + 2$  digits)
- . Input Voltage: 110 ~ 127VAC  $\pm 10\%/60Hz$ , 220 ~ 240VAC  $\pm 10\%/50Hz$   
Switchable



**M10-SP3003LX**

Model	Voltage	Current	Fixed output	Dimensions(W×H×D)	Weight(kg)
M10-SP3003LX	0~30V	0~3A	5V/1A	130×160×310mm	5
M10-SP3005LX	0~30V	0~5A	5V/1A	130×160×310mm	6.3
M10-SP6003LX	0~60V	0~3A	5V/1A	130×160×310mm	6.5

## M10-TPH SERIES

### Features

- . Voltage/Current preset function
- . New panel design
- . Two adjustable outputs & one fixed output
- . Cooling with the fan at back (M10-TP3005H)

### Specifications

- . Line Regulation:  $CV \leq 1 \times 10^{-4} + 3mV$   
 $CC \leq 2 \times 10^{-3} + 3mA$
- . Load Regulation:  $CV \leq 1 \times 10^{-4} + 2mV$   
 $CC \leq 2 \times 10^{-3} + 3mA$
- . Ripple & Noise:  $CV \leq 0.5mV$  rms  
 $CC \leq 3mA$  rms
- . Display Accuracy: Voltmeter  $\pm(0.2\%Rdg + 2$  digits)  
Ammeter  $\pm(1.0\%Rdg + 2$  digits)
- . Input Voltage: 110 ~ 127VAC  $\pm 10\%/60Hz$ , 220 ~ 240VAC  $\pm 10\%/50Hz$   
Switchable



**M10-TP3003H**

Model	Voltage	Current	Fixed output	Dimensions (W × H × D)	Weight (kg)
M10-TP3003H	0~30V×2	0~3A×2	5V/3A	260×160×370mm	8
M10-TP3005H	0~30V×2	0~5A×2	5V/3A	260×160×370mm	10